accucold

EL11LT



Product Features:

-45º capable Low temperature operation is ideal for a variety of laboratory, life science, and industrial applications Commercially approved UL-S listed to NSF/ANSI-7 standards 4 1/2" thick walls for added efficiency and stable cooling Extra thick insulation Factory installed lock Keyed lock on the handle for reliable security Pre-installed probe hole Factory-installed 1/2" probe hole located on the right side to accept user-provided monitoring equipment Digital thermostat Electronic controls for precise temperature management, with temperature readout and controls externally located for added convenience Counterbalanced hinges Easy and safe loading and unloading with a lid that remains open when lifted past 45° angles Casters Four solid wheels included for optional mobility Manual defrost Static cooling for a stable interior

33.5" x 28.5" x 27.25" (H x W x D)

Commercial -45° C capable chest freezer with digital thermostat and 4.8 cu.ft. capacity

Highlights:

Capable of -45° C operation for select laboratory and industrial storage purposes

UL-S listed to NSF-7 commercial standards

Digital thermostat with external controls allows easy and precise temperature monitoring

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



⁄ www.summitappliance.com

accucold

EL11LT Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	28.5" (72 cm)
Depth	27.25" (69 cm)
Depth with Handle	28.75" (73 cm)
Capacity	4.8 cu.ft. (136 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	7.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Shipping Weight	127.0 lbs. (58 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101023472
Freezer	
Reversible	No
Thermostat Type	Digital
Refrigerant Type	R290a
Refrigerant Amount	1.94 oz.
High Side PSI	342.0
Low Side PSI	174.0



