accuc@ld

ARG1PVDL2B



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. compact glass door all-refrigerator for vaccine storage with factoryinstalled data logger

Highlights:

NIST calibrated DDL included for accurate temperature logging

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC senso in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C	
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our webiste	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment	

accuc@ld

ARG1PVDL2B Specifications:

Overview		
Height of Cabinet	21.5" (55 cm)	
Width	17.5" (44 cm)	
Width with Door Open	18.0" (46 cm)	
Depth	19.75" (50 cm)	
Depth with Handle	21.5" (55 cm)	
Depth with door at 90°	36.0" (91 cm)	
Capacity	1.0 cu.ft. (28 L)	
Defrost Type	Automatic	
Door	Glass	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	0.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	63.0 lbs. (29 kg)	
Shipping Weight	73.0 lbs. (33 kg)	
Estimated Time to Ship	1 to 2 days	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
Refrigerator Features		
Door Swing	RHD	
Reversible	Factory Reversible	
Shelf Type	Wire	
Shelf Qty	3	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	0.71oz.	
Interior Light	Yes	
Temperature Range	2 to 8°C	
Dimensions		
Interior Height	15.75" (40 cm)	
Interior Width	14.0" (36 cm)	
Interior Depth	8.0" (20 cm)	



