accucold

ARG3MLDL2B



34" x 18.5" x 19" (H x W x D)

Performance series Med-Lab 3 cu.ft. counter height glass door all-refrigerator for laboratory storage with factoryinstalled data logger, a hospital grade cord with 'green dot' plug, and antimicrobial silver-ion handle

Highlights:

NIST calibrated DDL included for accurate temperature logging

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our webiste
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +10°C
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Purpose-built design	Designed and purpose-built to meet the demanding needs of scientific, life science, laboratory, and medical cold storage applications

Accessory torvision, FELIX STORCH, INC. | IS to Studies a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-8934 Serie pravided 4700 Britsring equipmer info@accucold.com

accucold

ARG3MLDL2B Specifications:

Height of Cabinet	34.0" (86 cm)
Width	18.5" (47 cm)
Width with Door Open	19.0" (48 cm)
Depth	19.0" (48 cm)
Depth with Handle	20.75" (53 cm)
Depth with door at 90°	36.0" (91 cm)
Capacity	3.0 cu.ft. (85 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	85.0 lbs. (39 kg)
Shipping Weight	95.0 lbs. (43 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101065755
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
	1.06oz.
Refrigerant Amount	
Interior Light	Yes
	Yes 2 to 10°C
Interior Light	
Interior Light Temperature Range	
Interior Light Temperature Range Dimensions	2 to 10°C
Interior Light Temperature Range Dimensions Interior Height	2 to 10°C 28.38" (72 cm)
Interior Light Temperature Range Dimensions Interior Height Interior Width	2 to 10°C 28.38" (72 cm) 15.25" (39 cm)

Compressor Step Depth

