accucold

Product Features:

ARG15MLLOCKER



72" x 23.38" x 24.38" (H x W x D)

Performance series Med-Lab 15 cu.ft. upright glass door all-refrigerator with 8 interior lockers, with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Designed and purpose-built to meet the demanding needs of scientific, life science, laboratory, and medical cold storage applications
The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs
Intuitive controls let you adjust the interior temperature between +2 to +10°C
Visual and audible alarms alert if the interior temperature rises or falls out of set range
Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)
-


ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799



accucold

ARG15MLLOCKER Specifications:

Overview	
Height of Cabinet	72.0" (183 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	24.38" (62 cm)
Depth with Handle	26.13" (66 cm)
Depth with door at 90°	46.5" (118 cm)
Capacity	15.0 cu.ft. (425 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	240.0 lbs. (109 kg)
Shipping Weight	250.0 lbs. (113 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101074986
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Lockers
Shelf Qty	8
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	2.65oz.
Interior Light	Yes
Temperature Range	2 to 10°C
Dimensions	
Interior Height	63.25" (161 cm)
Interior Width	20.0" (51 cm)
Interior Depth	17.0" (43 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)





accucold

