accucold

ARS12MLMCLK



61.75" x 23.38" x 24.38" (H x W x D)

Purpose-built all-refrigerator for breast milk storage with 6 interior locking compartments, antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

Highlights:

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

Purpose-built design	Designed and purpose-built for breast milk storage
Locking compartments	Six interior lockers sized at 11" H x 9 $3/8$ " W x 15 $1/4$ " D accommodate standard and oversized nursing bottles and travel bags for individual privacy
Combination locks	Allows each mother her own access system for added security
Combination lock override	Locks can be reset or accessed by staff/managers as needed (2 keys included)
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs
Adjustable temperature	Intuitive controls let you adjust the interior temperature between 33 to 40°F
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management
Factory-installed lock	Keyed locked near top of door for added security (2 keys included)
Access port (probe)	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment


ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com

accucold

ARS12MLMCLK Specifications:

Height of Cabinet	61.75" (157 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	24.38" (62 cm)
Depth with Handle	26.13" (66 cm)
Depth with door at 90°	46.5" (118 cm)
Capacity	12.0 cu.ft. (340 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	215.0 lbs. (98 kg)
Shipping Weight	225.0 lbs. (102 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101066578
Defeiseret en Erstunge	
Refrigerator Features	
Door Swing	RHD
-	RHD No
Door Swing	
Door Swing Reversible	No
Door Swing Reversible Shelf Type	No Lockers
Door Swing Reversible Shelf Type Thermostat Type	No Lockers Digital
Door Swing Reversible Shelf Type Thermostat Type Fan Type	No Lockers Digital Interior
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type	No Lockers Digital Interior R600a
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	No Lockers Digital Interior R600a 2.11oz.
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light	No Lockers Digital Interior R600a 2.11oz. Yes
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range	No Lockers Digital Interior R600a 2.11oz. Yes
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions	No Lockers Digital Interior R600a 2.11oz. Yes 33 to 40⁰F
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions Interior Height	No Lockers Digital Interior R600a 2.11oz. Yes 33 to 40°F 53.0" (135 cm)
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions Interior Height Interior Width	No Lockers Digital Interior R600a 2.11oz. Yes 33 to 40°F 53.0" (135 cm) 20.0" (51 cm)
Door Swing Reversible Shelf Type Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions Interior Height Interior Width Interior Depth	No Lockers Digital Interior R600a 2.11oz. Yes 33 to 40°F 53.0" (135 cm) 20.0" (51 cm) 17.0" (43 cm)



ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799