# accucold

# **ARS6MLMCLK**



### 32" x 23.38" x 24.38" (H x W x D)

Purpose-built all-refrigerator for breast milk storage with 2 interior locking compartments, antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

#### **Highlights:**

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

## **Product Features:**

Purpose-built design	Designed and purpose-built for breast milk storage
Locking compartments	Two interior lockers sized at 11" H x 9 $3/8$ " W x 15 $1/4$ " D accommodate standard and oversized nursing bottles and travel bags for individual privacy
Combination locks	Allows each mother her own access system for added security
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs
Combination lock override	Locks can be reset or accessed by staff/managers as needed (2 keys included)
Adjustable temperature	Intuitive controls let you adjust the interior temperature between 33 to 40°F
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management
Reversible door	User-friendly reversible door for increased flexibility; NOTE: Reversing the door will undo the self-closing door function
Factory-installed lock	Keyed locked near top of door for added security (2 keys included)

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com



# accucold

## **ARS6MLMCLK Specifications:**

Overview		
Height of Cabinet	32.0" (81 cm)	
Width	23.38" (59 cm)	
Width with Door Open	23.88" (61 cm)	
Depth	24.38" (62 cm)	
Depth with Handle	26.13" (66 cm)	
Depth with door at 90°	46.5" (118 cm)	
Capacity	6.0 cu.ft. (170 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	130.0 lbs. (59 kg)	
Shipping Weight	140.0 lbs. (64 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101066639	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Lockers	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	1.66oz.	
Interior Light	Yes	
Temperature Range	33 to 40°F	
Sound Level	36.4 dB	
Dimensions		
Interior Height	24.5" (62 cm)	
Interior Width	20.0" (51 cm)	
Interior Depth	17.0" (43 cm)	
Compressor Step Height	6.5" (17 cm)	
Compressor Step Width	20.0" (51 cm)	
Compressor Step Depth	5.0" (13 cm)	

