accucold

ARG6PV-CRT



32.5" x 23.38" x 24.38" (H x W x D)

Performance series 6 cu.ft. freestanding ADA compliant upright glass door controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to $77^{\circ}F$ (preset to $72^{\circ}F)$

Intelligent microprocessor digital temperature controller

Product Features:

Controlled Room Temperature Cabinet	Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at $72^{\circ}F$	
Purpose-built design	Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
+/-1.5°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Stable operation	Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +68 to +77°F	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Remote alarm contacts		

Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable

accucold

ARG6PV-CRT Specifications:

Overview			
Height of Cabinet	32.5" (83 cm)		
Width	23.38" (59 cm)		
Width with Door Open	23.88" (61 cm)		
Depth	24.38" (62 cm)		
Depth with Handle	26.13" (66 cm)		
Depth with door at 90°	46.5" (118 cm)		
Capacity	6.0 cu.ft. (170 L)		
Defrost Type	Automatic		
Door	Glass		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	0.75		
Voltage/Frequency	115 V AC/60 Hz		
Weight	119.0 lbs. (54 kg)		
Shipping Weight	168.0 lbs. (76 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101090467		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Wire		
Shelf Qty	4		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior		
Refrigerant Type	R600a		
Refrigerant Amount	1.66oz.		
Interior Light	Yes		
Temperature Range	68 to 77°F (preset to 72°F)		
Dimensions			
Interior Height	24.5" (62 cm)		
Interior Width	20.0" (51 cm)		
-			

	ł
Interior Depth	17.0"
Compressor Step Height	6.5"
Compressor Step Width	20.0" 42
Compressor Step Depth	5.0"

