accucold

ARS15PV-CRT



72" x 23.38" x 24.38" (H x W x D)

Performance series 15 cu.ft. upright controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to $77^{\circ}F$ (preset to $72^{\circ}F)$

Intelligent microprocessor digital temperature controller

Product Features:

Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F	
Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Designed to maintain a set temperature, even when ambient room temperature is as cold as 68° F or as high as 86° F	
Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Intuitive controls let you adjust the interior temperature between +68 to +77°F	
Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	

Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable

accucold

ARS15PV-CRT Specifications:

Overview		
Height of Cabinet	72.0" (183 cm)	
Width	23.38" (59 cm)	
Width with Door Open	23.88" (61 cm)	
Depth	24.38" (62 cm)	
Depth with Handle	26.13" (66 cm)	
Depth with door at 90°	46.5" (118 cm)	
Capacity	15.0 cu.ft. (425 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	205.0 lbs. (93 kg)	
Shipping Weight	270.0 lbs. (122 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101090498	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wire	
Shelf Qty	7	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	2.65oz.	
Interior Light	Yes	
Temperature Range	68 to 77°F (preset to 72°F)	
Dimensions		
Interior Height	63.25" (161 cm)	
Interior Width	20.0" (51 cm)	

	6'-0"LG. ELEC. CORD			
		Dry contact	s	
Interior Depth	17.0" (43 cm)			
Compressor Step Height	6.5" (17 cm)	Compressor Housing	12	
Height	നമ		204	
Compressor Step Width	20.0" (81 cm)			
		2" Probe hole		
Compressor Step Depth	5.0" (13 cm)	TOP VIEW	1/2	
			49- 1- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2-	
	€ <u>4</u>	100		
	1	19		
		le l		
		Ĩ		
		le l		
		1		
		щ		



accucold



