accuc@ld

ARS18PV-CRT



78.5" x 27.5" x 26" (H x W x D)

Performance series 18 cu.ft. upright controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to $77^{\circ}F$ (preset to $72^{\circ}F$)

Intelligent microprocessor digital temperature controller

Product Features:

Controlled Room Temperature Cabinet	Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F	
Purpose-built design	Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
+/-1.5°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Stable operation	Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +68 to +77°F	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle ### Automatic defrost with adjustable cycle #### Automatic defrost with adjustable cycle ###################################	1 🕰	

accuc@ld

ARS18PV-CRT Specifications:

Overview		
Height of Cabinet	78.5" (199 cm)	
Width	27.5" (70 cm)	
Width with Door Open	28.0" (71 cm)	
Depth	26.0" (66 cm)	
Depth with Handle	27.75" (70 cm)	
Depth with door at 90°	52.0" (132 cm)	
Capacity	18.0 cu.ft. (510 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	1.5	
Voltage/Frequency	115 V AC/60 Hz	
Weight	275.0 lbs. (125 kg)	
Shipping Weight	300.0 lbs. (136 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101090504	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wire	
Shelf Qty	7	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R290a	
Refrigerant Amount	1.75oz.	
High Side PSI	280.0	
Low Side PSI	90.0	
Wheel Qty	4	
Interior Light	Yes	
Temperature Range	68 to 77°F (preset to 72°F)	

Dimensions	
Interior Height	68.5" (174 cm)
Interior Width	24.13" (61 cm)
Interior Depth	18.75" (48 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	24.13" (61 cm)
Compressor Step Depth	6.5" (17 cm)



