## accuc@ld

# **ARS3PV-CRT**



34" x 18.5" x 19" (H x W x D)

Performance series 3 cu.ft. upright controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

### **Highlights:**

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to 77°F (preset to 72°F)

Intelligent microprocessor digital temperature controller

#### **Product Features:**

Controlled Room Temperature Cabinet	Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at $72^{\text{o}}\text{F}$	
Purpose-built design	Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
+/-1.5°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Stable operation	Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
ACTOSOLD DIVISION, FELIX STORCH, INC.   770 Garrison Avenue Bronx, NY 10474 USA TEL 718	1 /2-	

## accuc@ld

### **ARS3PV-CRT Specifications:**

Overview		
Height of Cabinet	34.0" (86 cm)	
Width	18.5" (47 cm)	
Width with Door Open	19.0" (48 cm)	
Depth	19.0" (48 cm)	
Depth with Handle	20.75" (53 cm)	
Depth with door at 90°	36.0" (91 cm)	
Capacity	3.0 cu.ft. (85 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	0.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	77.0 lbs. (35 kg)	
Shipping Weight	113.0 lbs. (51 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101090535	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wire	
Shelf Qty	4	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	1.06oz.	
Interior Light	Yes	
Temperature Range	68 to 77°F (preset to 72°F)	
Dimensions		
Interior Height	28.38" (72 cm)	
Interior Width	15.25" (39 cm)	



