accuc@ld

ARS62MLMCBIADALK



31.75" x 23.38" x 25" (H x W x D)

Purpose-built MOMCUBE™ all-refrigerator for breast milk storage designed for freestanding or recessed installation, with 2 interior locking compartments, antimicrobial silverion handle, and hospital grade 'green dot' plug

Highlights:

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Meets CDC guidelines with a temperature range of 33°F to 40°F

Product Features:

Purpose-built design	Designed and purpose-built for breast milk storage	
ADA compliant	Just under 32" tall designed to fit under ADA compliant counters	
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use	
Locking compartments	Two interior lockers sized at 11" H x 9 $3/8$ " W x 15 $1/4$ " D accommodate standard and oversized nursing bottles and travel bags for individual privacy	
Combination locks	Allows each mother her own access system for added security	
Combination lock override	Locks can be reset or accessed by staff/managers as needed (2 keys included)	
Fully finished white cabinet	Allows the unit to be used freestanding	
Adjustable plastic-coated wire shelves for improved circulation	Shelves can be positioned with a front lip for small storage items or reversed to a flat position to better hold larger items, with multiple shelf positions spaced at 1/2" to accommodate virtually any size	
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management	



accuc@ld

ARS62MLMCBIADALK Specifications:

Height of Cabinet 31.75" (81 cm) Width 23.38" (59 cm) Width with Door Open 23.88" (61 cm)	cm)		
Width with Door Open 23.88" (61 o			
Danish of all (a)	cm)		
Depth 25.0" (64 c	cm)		
Depth with Handle 26.75" (68 d	cm)		
Depth with door at 90° 47.0" (119 c	cm)		
Capacity 6.0 cu.ft. (170) L)		
Defrost Type Autom	atic		
Door WI	nite		
Cabinet WI	nite		
US Electrical Safety E	TL		
Canadian Electrical ETI Safety	C		
Amps 0	.75		
Voltage/Frequency 115 V AC/60	Hz		
Weight 135.0 lbs. (61	kg)		
Shipping Weight 146.0 lbs. (66	kg)		
Parts & Labor Warranty 2 Ye	ars		
Compressor Warranty 5 Ye	ars		
UPC 761101078	700		
Refrigerator Features			
Door Swing R	HD		
Reversible	Yes		
Shelf Type Lock	Lockers		
Shelf Qty	2		
Adjustable Shelves	Yes		
Thermostat Type Dig	jital		
Fan Type Inte	rior		
Refrigerant Type R60	00a		
Refrigerant Amount 1.66	oz.		
High Side PSI 28	0.0		
Low Side PSI 9	0.0		
Interior Light	Yes		
Temperature Range 33°F to 4	0°F		
Dimensions			
Dimensions Interior Height 24.5" (62 c	cm)		
	<u> </u>		

Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.0" (13 cm)

