## accucold

# **ARS6PV-CRT**



#### 32.5" x 23.38" x 24.38" (H x W x D)

Performance series 6 cu.ft. freestanding ADA compliant upright controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

#### **Highlights:**

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to  $77^{\circ}F$  (preset to  $72^{\circ}F)$ 

Intelligent microprocessor digital temperature controller

#### **Product Features:**

Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72⁰F
Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products
The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F
Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs
Intuitive controls let you adjust the interior temperature between +68 to +77°F
Visual and audible alarms alert if the interior temperature rises or falls out of set range
Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)

Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Activities Adjustable

## accucold

### **ARS6PV-CRT Specifications:**

Overview	
	20 E!! (02 cm)
Height of Cabinet	32.5" (83 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	24.38" (62 cm)
Depth with Handle	26.13" (66 cm)
Depth with door at 90°	46.5" (118 cm)
Capacity	6.0 cu.ft. (170 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.75
Voltage/Frequency	115 V AC/60 Hz
Weight	109.0 lbs. (49 kg)
Shipping Weight	158.0 lbs. (72 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101090559
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.66oz.
Interior Light	Yes
Temperature Range	68 to 77°F (preset to 72°F)
Dimensions	
Interior Height	24.5" (62 cm)
Interior Width	20.0" (51 cm)

